



BEARING CORP.OF AMERICA



3.15 Inch | 80 Millimeter x 6.693 Inch | 170
Millimeter x 1.535 Inch | 39 Millimeter NSK
7316BYG Angular Contact Ball Bearings

Bearing No. 7316BYG

7316BYG Bearing 2D drawings and 3D CAD models

| | |
|---------------------------------|---|
| Category | Angular Contact Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight | 4 |
| EAN | 0029176019258 |
| Product Group | B00308 |
| Enclosure | Open |
| Flush Ground | Yes |
| Rolling Element | Ball Bearing |
| Number of Rows of Balls | Single Row |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Snap Ring | No |
| Cage Material | Brass |
| Contact Angle | 40 Degree |
| Internal Clearance | C0-Medium |
| Number of Bearings | 1 (Single) |
| Mounting Arrangement | Universal |
| Inch - Metric | Metric |
| Long Description | 80MM Bore; 170MM Outside Diameter; 39MM Width; Open; Yes Flush Ground; Ball Bearing; Single |



BEARING CORP.OF AMERICA

| | |
|-------------------------------|---|
| | Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring |
| Category | Angular Contact Ball Bearing |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact |
| Manufacturer URL | http://www.nskamericas.com |
| Manufacturer Item Number | 7316BYG |
| Weight / LBS | 4 |
| D | 6.693 Inch 170 Millimeter |
| B | 1.535 Inch 39 Millimeter |
| d | 3.15 Inch 80 Millimeter |
| bore diameter: | 80 mm |
| operating temperature range: | Maximum of +120 ° C |
| outside diameter: | 170 mm |
| cage material: | Brass |
| overall width: | 39 mm |
| outer ring width: | 39 mm |
| contact angle: | 40 ° |
| maximum rpm: | 4300 RPM |
| row type & fill slot: | Single-Row Non-Fill Slot |
| finish/coating: | Uncoated |
| internal clearance: | C0 |
| precision rating: | ABEC 1 (ISO Class Normal) |
| closure type: | Open |
| fillet radius: | 0.08 in |
| radial dynamic load capacity: | 32575 lb |
| | |



BEARING CORP.OF AMERICA

| | |
|------------------------------|----------|
| series: | 7300 |
| radial static load capacity: | 22500 lb |