



# BEARING CORP.OF AMERICA



4.331 Inch | 110 Millimeter x 9.449 Inch | 240  
Millimeter x 1.969 Inch | 50 Millimeter NSK  
7322BMG Angular Contact Ball Bearings

Bearing No. 7322BMG

7322BMG Bearing 2D drawings and 3D CAD models

|                                 |  |
|---------------------------------|--|
| Category                        | Angular Contact Ball Bearings  |
| Inventory                       | 0.0  |
| Manufacturer Name               | NSK  |
| Minimum Buy Quantity            | N/A  |
| Weight                          | 11.2   |
| EAN                             | 0029176019319  |
| Product Group                   | B00308   |
| Enclosure                       | Open   |
| Flush Ground                    | Yes  |
| Rolling Element                 | Ball Bearing   |
| Number of Rows of Balls         | Single Row   |
| Precision Class                 | ABEC 1   ISO P0  |
| Maximum Capacity / Filling Slot | No   |
| Snap Ring                       | No   |
| Cage Material                   | Brass  |
| Contact Angle                   | 40 Degree  |
| Internal Clearance              | C0-Medium  |
| Number of Bearings              | 1 (Single)   |
| Mounting Arrangement            | Universal  |
| Inch - Metric                   | Metric   |
| Long Description                | 110MM Bore; 240MM Outside Diameter; 50MM Width; Open; Yes Flush Ground; Ball Bearing; Single |



## BEARING CORP.OF AMERICA

|                          |   |
|--------------------------|---|
|                          | Row of Balls; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Brass Cage; 40 Degree; 1 (Single); |
| Category                 | Angular Contact Ball Bearing  |
| UNSPSC                   | 31171531  |
| Harmonized Tariff Code   | 8482.10.50.28   |
| Noun                     | Bearing   |
| Keyword String           | Angular Contact   |
| Manufacturer URL         | <a href="http://www.nskamericas.com">http://www.nskamericas.com</a>   |
| Manufacturer Item Number | 7322BMG   |
| B                        | 1.969 Inch   50 Millimeter  |
| d                        | 4.331 Inch   110 Millimeter   |
| D                        | 9.449 Inch   240 Millimeter   |