



BEARING CORP.OF AMERICA



SKF NSK Koyo NTN Ball Bearing 6000 Zz 6001
 6002 6003 6004 6005 6006 6007 6008 6009 6010
 6021 6022 6023 6024 for
 Motorcycle/Engine/Electric
 Motor/Pump/Generator

Bearing No. 6000

6000 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 10x26x8 mm |
| Bore Diameter | 10 mm |
| Outer Diameter | 26 mm |
| Width | 8 mm |
| d | 10 mm |
| D | 26 mm |
| B | 8 mm |
| C | 8 mm |
| r min. | 0,3 mm |
| da min. | 12 mm |
| Da max. | 24 mm |
| ra max. | 0,3 mm |
| Weight | 0,019 Kg |
| Basic dynamic load rating (C) | 4,55 kN |
| Basic static load rating (C0) | 1,95 kN |
| (Grease) Lubrication Speed | 31000 r/min |
| (Oil) Lubrication Speed | 36000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | KOYO |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.02 |
| | |



BEARING CORP.OF AMERICA

| | |
|---------------------------------|---|
| Product Group | B00308 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 10MM Bore; 26MM Outside Diameter; 8MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.koyousa.com |
| Manufacturer Item Number | 6000 |
| Weight / LBS | 0.045 |
| Outside Diameter | 1.024 Inch 26 Millimeter |
| Outer Race Width | 0.315 Inch 8 Millimeter |
| Bore | 0.394 Inch 10 Millimeter |
| Bearing No. | 6000 |
| r(min) | 0.3 |
| Cr | 5.70 |
| C0r | 1.95 |
| Cu | 0.100 |
| | |



BEARING CORP.OF AMERICA

| | |
|------------------|-------|
| f0 | 12.3 |
| Grease lub. | 31000 |
| Oil lub. | 36000 |
| da(min) | 12 |
| Da(max) | 24 |
| ra(max) | 0.3 |
| (Refer.)Mass(kg) | 0.019 |